

Christie HS Series

D13WU-HS / D13HD-HS

Enterprise venues and boardrooms
Entertainment venues
Fixed installation
Houses of worship

Hotels
Live events and conferences
Rental and staging
Trade shows and exhibitions



Brilliant colors at a brilliant price

When color accuracy and affordability are key, choose the Christie® D13WU-HS or D13HD-HS 1DLP® laser projector. Producing 13,000 lumens, HD or WUXGA resolution and featuring patented Christie BoldColor Technology, visuals are vibrant and true-to-life when compared to standard laser phosphor projectors.

With built-in camera-based warping and blending, these projectors are easy to set up, whether on their own or as part a multi-projector array. Their compact and lightweight form factor, omnidirectional capabilities and optional rigging frame make the D13WU-HS and D13HD-HS perfect options for challenging installation spaces.

CHRISTIE®

		Christie D13WU-HS	Christie D13HD-HS
Image	brightness (lumens)	• 13,500 ISO • 12,500 Center • 12,000 ANSI	• 13,000 ISO • 12,000 Center • 11,500 ANSI
	color wheel	• 4 segment (RGBY) – 2X or 3X speed	
	contrast	• Full on/off (Christie RealBlack enabled): 750,000:1 • Dynamic contrast: 7500:1 (WU), 6500:1 (HD) • Full on/off (Christie RealBlack disabled): 1200:1 • 250:1 ANSI	
Display technology	type	• 1 x 0.96" DMD	• 1 x 0.95" DMD
	native resolution	• 1920 x 1200 (2,304,000 pixels) 16:10	• 1920 x 1080 (2,073,600 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor Technology	
	typical lifetime	• 20,000 hrs	
Signal inputs	standard	• HDMI x 2 (one on rear panel, one on bottom of projector, independently selectable) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • HD15 x 1 • USB x 1 (Type B mini) • Display over USB • HDBaseT (RJ45 x 1) • USB x 1 (Type A) • Image Viewer or Wi-Fi@ dongle (optional) • RJ45 x 1 (Christie Presenter over wired network connection)	
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs	
	3D	• HDMI 1.4, HDBaseT – frame packed, top/bottom, side-by-side (up to 120Hz output) • 3D sync in (BNC) – for genlocking projectors • 3D sync out (BNC) – for genlocking projectors, or controlling emitters	
	scan rates	• Horizontal: 15kHz to 91kHz • Vertical: 24Hz to 85Hz	
Signal outputs	• 3GSDI x 1 (BNC) • DVI-D x 1 (digital only)		
Control and networking	• RS-232 in • Control via HDBaseT • Ethernet (100BaseT) RJ45 with ChristieNET™ connectivity • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Loop out available for daisy chaining		
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS)	
	offsets for full ILS lenses	• ±120% Vertical (±720 pixels) • ±50% Horizontal (±480 pixels)	• ±133% Vertical (±720 pixels) • ±50% Horizontal (±480 pixels)
	offsets for 0.84-1.02:1	• +37/-60% Vertical (+222/-363 pixels) • +15/-44% Horizontal (+152/-426 pixels)	• +110/-86% Vertical (+596/-466 pixels) • +34/-39% Horizontal (+330/-376 pixels)
	offsets for 1.02-1.36:1	• +51/-53% Vertical (+307/-318 pixels) • +11/-50% Horizontal (+107/-480 pixels)	• +125/-98% Vertical (+676/-534 pixels) • +42/-47% Horizontal (+408/-457 pixels)
Accessories	standard	• IR remote w/wired remote jack (wire not included) • AC line cord for projector head • User manual	
	optional	• Christie One Rigging Frame • Lens adapter for E Series lenses • 1DWUSB-BGN (wireless dongle for video and control) • Christie HS Series fog filter refills (1 set) • Christie HS Series fog filter covers and filters (order once per projector then only filter refills) • Christie One Mount Plus • One Mount Extender Rod • Replacement remote control • One Mount Rigging Kit (used with One Mount, One Mount Plus and/or One Mount Extender Rod)	
Power requirements	operating voltage	• Normal: 100-120 VAC/200-240 VAC; 60/50Hz	
	power consumption	• Normal mode: 1220W ±15% (200 VAC), 1300W ±15% (100 VAC) • ECO1 mode: 1000W ±15% (220 VAC), 1050W ±15% (100 VAC) • ECO2 mode: 660W ±15% (220 VAC), 700W ±15% (100 VAC)	
	operating current	• Normal mode: 7A (200-240 VAC), 14A (100-120 VAC)	
	dissipation	• Normal mode: 4435 BTU/hr • ECO1 mode: 3580 BTU/hr • ECO2 mode: 2390 BTU/hr	
Audible noise	• Typical: 39dBA • Eco mode: 37dBA		
Physical	size	• (L x W x H) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L x W x H) 36.4 x 33.3 x 20.2" (925 x 845 x 515mm)	
	weight (w/o lens)	• 93.7lbs (42.5kg)	
	shipping weight	• 127lbs (57.5kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 0-85% non-condensing	
Regulatory	• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • RoHS, REACH, WEEE		

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Columbia
ph: +57 (318) 447 3179

Eastern Europe
ph: +36 (0) 1 47 48 138

France
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)
ph: +49 221 99 512-0

Germany (Moechengladbach)
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan
ph: +81 3 3599 7481

Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000

Singapore
ph: +65 6877 8737

South Korea
ph: +82 2 702 1601

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 (0) 4 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

Independent sales
consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

Printed in Canada on recycled paper. 4693 May 18

CHRISTIE®