

DWU600-G



Key Features

- 6,050 lumens Brightness
- 4800:1 Contrast
- WUXGA (1920x1200) Wide resolution
- 0.67" 1Chip DMD
- 15.3kg (without lens)
- Motorized zoom, focus and lens shift
- Edge blending
- Lens memory, Mechanical Shutter
- Twin color wheel system changing from Top cover



Specification

모델명 (Model Name)		DWU600-G
투사방식 (Display Technology)		0.67" 1Chip DMD
밝기 (Brightness)		6,050 lumens
명암비 (Contrast)		4800:1
해상도 (Native resolution)		WUXGA 1920x1200
화면비 (Aspect ratio)		16:10
램프 (lamp)	램프번호 (Part Number)	003-004808-XX
	타입 (Type)	465W
	수명 (Lifetime)	2500 hrs(Eco) / 2000 hrs(Normal)
렌즈 (Lens)	렌즈 (Lens)	140-100102-XX
	투사비율 (Throw ratio)	1.22-1.52:1
	렌즈쉬프트 (Lens shift)	Vertical ±100% Horizontal ±20%
	키스톤 (Keystone)	상하좌우
	줌 (Zoom)	Powered
	포커스 (Focus)	Powered
중형왜곡보정 (Geometric correction)		-
화면사이즈 (Diagonal)		50 ~ 300"
입력단자 (Input)		1 X 3RCA(Component) 1 X RCA(Composite) 1 X S-VIDEO 1 X Displayport 1 X HDMI 1 X 15-pin mini D-sub(RGB) 1 X DVI-D
출력단자 (Output)		1 X 15-pin mini D-sub (RGB)
컨트롤/서비스 단자 (Control/Service)		2 X Φ 3.5 stereo jack (Remote, I/O) 1 X RS-232C 1 X RJ-45 1 X USB Type A 1 X USB Type mini B
입력 신호 (Input signal)		VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+ UXGA, WSXGA+, WUXGA, MAC16"
비디오 포맷 (Video Formats)		NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL (60Hz) 480i/p, 576i/p, 720p, 1080i/p
작동 온도 (Temperature)		5 ~ 35°C
스피커 (Speaker)		-
팬 소음 (Fan Noise)		-
정격 전압 (Operating voltage)		AC 100-240V, 50/60Hz
소비 전력 (Power consumption)		580W(Normal) / 480W(Eco) / 0.5W(Stand-by)
규격 (Size)		(W)435 x (H)207 x (D)388 mm
무게 (Weight)		15.3kg (without lens)

※ 제품의 외관 및 사양은 성능 개선을 위해 사전 예고 없이 변경될 수 있습니다.