

# MP-V5002

## Introducing Our Very Latest 3LCD Laser Projector



**Introducing our innovative 3LCD Laser MP-V5002 projector which combines all our technical expertise with our market leading knowledge.**

This new, portable projector can produce 5,000 ANSI, has a 1,500,000:1 contrast ratio, a resolution of 1920 x 1200 and will provide 20,000 hours of maintenance-free operation.

So whatever the situation, our MP-V5002 projector is the perfect solution for today's professionals. It combines simple usability with powerful performance in a lightweight and compact design, enabling users to set it up and get working in seconds.

### Key Features:

WUXGA 1920 x 1200 resolution

5,000 ANSI lumens white / Colour light output

1,500,000:1 contrast ratio

Images up to 235" diagonal

360° Flexible installation

Accentualizer and HDCR

Please note: This is a preliminary data sheet. Content, technical specifications and images are subject to change.

# MP-V5002 3LCD Laser Projector

## Technical Specifications

<b>Panel Size</b>	3LCD 16mm (0.64")
<b>Panel Structure</b>	3LCD
<b>Resolution</b>	WUXGA (1920 x 1200)
<b>Light Output (Brightness) ANSI Lumens</b>	5,000 (Normal)
<b>Contrast Ratio</b>	1,500,000:1
<b>Light Source Life (Hours)</b>	20,000
<b>Lens</b>	Built-in
<b>Lens Zoom</b>	Fixed
<b>Lens Focus</b>	Manual focus
<b>Projection Lens F Number</b>	1.8
<b>Focus Distance</b>	0.7 - 2.9
<b>Distance to Width Ratio/ Throw Ratio (:1)</b>	0.56
<b>Diagonal Display Size</b>	60 - 235"
<b>Installation</b>	Ceiling, Tabletop, Rear, Portrait, 360° Projection
<b>Speakers</b>	16W mono
<b>Digital Keystone Correction (Degrees)</b>	Horizontal ± 30°, Vertical ± 30°
<b>Picture Modes</b>	Standard, Natural, Cinema, Dynamic, Whiteboard, DICOM SIM, User-1, User-2, User-3
<b>Picture Adjustments</b>	ASPECT selection (Normal/4:3/16:9/16:10/14:9/Zoom/ Native), Perfect Fit (4 corners and 4 sides), Frame Lock (Data signal with vertical frequency of 49 to 51Hz, 59 to 61Hz), HDCR, Image blank by RS232C/Remote control, Image optimizer, Magnify, Mirror reverse image, Up-side down image
<b>Operating Features</b>	Keystone V/H, PerfectFit, Standby audio, Audio pass through, Cloning function, Easy schedule setting, Auto power on
<b>Network Features</b>	Wireless Capability(Optional), Multi Projector, Moderator Control Mode, Projector Quick Connection (iOS / Android app), Projector Monitoring and Control from a Remote Location, E-mail Alerts
<b>Security Features</b>	Password/Myscreen Password, Pin Lock, Key Lock
<b>Supported Languages</b>	34 Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew)
<b>Digital Input</b>	HDMI x 3 (HDCP compliant, HDMI 1 shared with MHL)
<b>Analogue Input</b>	15-pin Mini-D-Sub x 2, RCA Jack x 1
<b>Video Output</b>	15 pin Mini D-Sub x 1 (shared with analog computer input)
<b>Audio Input</b>	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1
<b>Audio Output</b>	3.5mm Stereo Mini Jack x 1
<b>RS-232C Control</b>	1 x 9-pin D-Sub
<b>Wireless LAN</b>	USB-WL-5G wireless adaptor (optional)
<b>Wired LAN</b>	RJ45 connector x 1
<b>USB Type-A</b>	USB Type A x 2 (PC less Presentation or Wireless adaptor)
<b>USB Type B</b>	USB Type B x 1 (USB display or USB mouse control)
<b>Power Supply</b>	AC 100V - 120V / AC 220V - 240V (50/60Hz)
<b>Operating Power Consumption</b>	370W / 360W
<b>Standby Power Consumption</b>	Less than 0.5W

<b>Weight</b>	8.1kg
<b>Dimensions (W x H x D)</b>	506 x 136 x 424 mm
<b>Noise (Normal)</b>	34dB (Normal), 28dB (Whisper)
<b>Certification</b>	CE Marking, EN61000-3-2, EN61000-3-3, EN55032 (Class A), EN55035 (EMC Directive), EN60950-1 (Low Voltage Directive), WEEE/RoHS compliant, KC
<b>Computer</b>	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA, WUXGA
<b>Video</b>	525i(480i), 525p(480p), 625i(576i), 625p(576p), 1125i(1080i@50/60), 1125p(1080p@50/60)
<b>Supplied Accessories</b>	Power Cable (1.8m), Computer Cable (2m), Remote Control Unit x1, Concise User Manual x1, Security Label x1, Adapter Cover x1, Hook Metal x1, Screw x1, HDMI Cable Holder (x2), Cable Tie (large x1, medium x2, small x1), AA Batteries x2
<b>Optional Accessories</b>	USB wireless adaptor USB-WL-5G
<b>Filter</b>	UX43251
<b>Remote Control</b>	HL03037



Dealer Stamp